

## SPRINKLER SERVICE AS REQUIRED NOTE

DOMESTIC FLOWS NOT PERMITTED FIRE SPRINKLER SYSTEMS ONLY

## NOTE

1. STANDARD CONFIGURATION SHOWN 2.ALTERNATIVE CONFIGURATION - BACKFLOW PREVENTION NOT REQUIRED OMIT TESTABLE DEVICE AND VALVES AND REPLACE WITH NON-TESTABLE SINGLE CHECK VALVE

## FIRE SERVICE MAIN NOTE

DOMESTIC FLOWS NOT PERMITTED HYDRANT PILLARS AND FIRE HOSE REELS ONLY

BYPASS PIPE SIZE TO BE 25mm FOR UP TO 3 FIRE HOSE REELS CONNECTED TO SERVICE BYPASS PIPE SIZE TO BE 40mm FOR MORE THAN 3 FIRE HOSE REELS CONNECTED TO SERVICE FOR ALTERNATIVE CONFIGURATION BYPASS PIPE SIZE TO SUIT

## DOMESTIC SERVICE AS REQUIRED NOTE

SIZE TO SUIT

APPROVED TAPPING BAND	
VALVE, BALL / BUTTERFLY, FLANGED / THREADED (TESTABLE DEVICE ISOLATION)	APPLICANT
DOMESTIC METER	
VALVE, BUTTERFLY / BALL, FLANGED / THREADED (METER ISOLATION)	
TESTABLE DEVICE	APPLICANT
VALVE, BUTTERFLY / BALL, FLANGED / THREADED (TESTABLE DEVICE ISOLATION)	APPLICANT
BY-PASS METER	
VALVE, BALL, THREADED, (METER ISOLATION) NORMALLY CLOSED (NC)	
VALVE, BUTTERFLY, (ISOLATION)	
TESTABLE DEVICE (BY APPLICANTS PLUMBER AS REQUIRED)	APPLICANT
VALVE, BUTTERFLY, (TESTABLE DEVICE ISOLATION)	APPLICANT
VALVE, BUTTERFLY, DIAMETER PER REQUIREMENTS	
VALVE, SLUICE, DNXX, ISOLATION FROM MAIN	
DESCRIPTION	BY
	VALVE, BALL / BUTTERFLY, FLANGED / THREADED (TESTABLE DEVICE ISOLATION) DOMESTIC METER VALVE, BUTTERFLY / BALL, FLANGED / THREADED (METER ISOLATION) TESTABLE DEVICE VALVE, BUTTERFLY / BALL, FLANGED / THREADED (TESTABLE DEVICE ISOLATION) BY-PASS METER VALVE, BALL, THREADED, (METER ISOLATION) NORMALLY CLOSED (NC) VALVE, BUTTERFLY, (ISOLATION) TESTABLE DEVICE (BY APPLICANTS PLUMBER AS REQUIRED) VALVE, BUTTERFLY, (TESTABLE DEVICE ISOLATION) VALVE, BUTTERFLY, (TESTABLE DEVICE ISOLATION) VALVE, BUTTERFLY, DIAMETER PER REQUIREMENTS VALVE, SLUICE, DNXX, ISOLATION FROM MAIN

DRAWING NO.

GRC-ED-016

A3 SHEET REVISION

A